

LED STRIP SPECIFICATION

2835 AC230V 120LED 2PIN 12MM WHITE LED STRIP SPECIFICATION

Product Model : 2835-ac230v-120led-2pin-12mm-w


PART 1 Product Specification



Electrical & Optical Parameters

Parameter	Value
Input Voltage	AC 230V
Current	/
Working Power	18 W/m
PCB Width	12 mm
Cut Length	100 mm (12 LEDs)
LED Type	SMD2835
LED Quantity	120 LEDs/m
LED Color	1800K – 20000K
Beam Angle	120°
Luminance	90 Lm/m
CRI (Ra)	> 80
Working Temperature	-20 °C – +60 °C
Storage Temperature	-20 °C – +60 °C
Waterproof Rating	IP66/IP68
Lifespan	> 50 000 hours


PART 2 Product Dimensions



PART 3 Color Standard

Color Temperature Reference

< 2200K	2700K	3000K	4000K	6000K	> 8000K
Super Warm White	Warm White	Warm White	Natural White	White	Cold White
<i>Candlelight</i>	<i>HPS Lamp</i>	<i>Halogen / Incandescent</i>	<i>Metal Halide</i>	<i>Pure White</i>	<i>Daylight</i>




Only one Bin LED is used for each order. The same Bin is maintained in subsequent orders to ensure colour consistency across batches.

PART 4 Production Application



PART 5 **Wiring Diagram**

1. Connection method one/接线方式一**2. Connection method two/接线方式二**


PART 6 Precautions



☐ Please cut it according to the cutting line, do not cut it at other positions.



☐ Please make sure the wall is dry and free of dust before pasting.



☐ Do not fold, twist or step on the led strips.



☐ The LED strip wire ends cannot be shorted together.

PART 7 Product Accessories



Power Supply




Connector



Weldless Connector




Controller



Aluminum profile

➤ Please purchase the above accessories according to your demand.

PART 8 **Packaging Instructions**



- Standard: 5m/roll, custom lengths supported
- No heavy stacking / stepping on cartons
- Check goods first if outer box damaged before signing