

LED STRIP SPECIFICATION

5050 DC12V 108LED 5PIN 12MM RGBW LED STRIP SPECIFICATION

Product Model : 5050-dc12v-108led-5pin-12mm-RGBW


PART 1 Product Specification




Electrical & Optical Parameters

Parameter	Value
Input Voltage	DC 12V
Current	1.83 A/m
Working Power	22 W/m
PCB Width	12 mm
Cut Length	27.77 mm (3 LEDs)
LED Type	SMD5050
LED Quantity	108 LEDs/m
LED Color	RGBW/WW
Beam Angle	120°
Luminance	495-540lm/W
CRI (Ra)	Ra>80
Working Temperature	-20 °C – +60 °C
Storage Temperature	-20 °C – +60 °C
Waterproof Rating	IP20/IP65/IP66/IP68
Lifespan	> 50 000 hours

PART 2 Product Dimensions





PART 3 Color Standard



PART 4 Production Application



PART 5 Wiring Diagram**1. Connection method one/接线方式一****2. Connection method two/接线方式二**


PART 6 Precautions



☐ Please cut it according to the cutting line, do not cut it at other positions.



☐ Please make sure the wall is dry and free of dust before pasting.



☐ Do not fold, twist or step on the led strips.



☐ The LED strip wire ends cannot be shorted together.

PART 7 Product Accessories



Power Supply




Connector



Weldless Connector




Controller



Aluminum profile

➤ Please purchase the above accessories according to your demand.

PART 8 **Packaging Instructions**



- Standard: 5m/roll, custom lengths supported
- No heavy stacking / stepping on cartons
- Check goods first if outer box damaged before signing