

LED STRIP SPECIFICATION

5050 DC24V 60LED 4PIN 10MM RGB LED STRIP SPECIFICATION

Product Model : 5050-dc24v-60led-4pin-10mm-RGB


PART 1 Product Specification



Electrical & Optical Parameters

Parameter	Value
Input Voltage	DC 24V
Current	0.6 A/m
Working Power	14.4 W/m
PCB Width	10 mm
Cut Length	100 mm (6 LEDs)
LED Type	SMD5050
LED Quantity	6 LEDs/100mm
LED Color	RGB
Beam Angle	120°
Luminance	/
CRI (Ra)	Ra>80
Working Temperature	-20 °C – +60 °C
Storage Temperature	-20 °C – +60 °C
Waterproof Rating	IP20 / IP65 / IP66 / IP68
Lifespan	> 50 000 hours


PART 2 Product Dimensions



PART 3 Color Standard


Color Temperature Reference

< 2200K	2700K	3000K	4000K	6000K	> 8000K
Super Warm White	Warm White	Warm White	Natural White	White	Cold White
<i>Candlelight</i>	<i>HPS Lamp</i>	<i>Halogen / Incandescent</i>	<i>Metal Halide</i>	<i>Pure White</i>	<i>Daylight</i>




Only one Bin LED is used for each order. The same Bin is maintained in subsequent orders to ensure colour consistency across batches.

PART 4 Production Application




PART 5 Wiring Diagram

1. Connection method one/接线方式一



2. Connection method two/接线方式二




PART 6 Precautions



☐ Please cut it according to the cutting line, do not cut it at other positions.



☐ Please make sure the wall is dry and free of dust before pasting.



☐ Do not fold, twist or step on the led strips.



☐ The LED strip wire ends cannot be shorted together.

PART 7 Product Accessories



Power Supply




Connector



Weldless Connector




Controller



Aluminum profile

➤ Please purchase the above accessories according to your demand.

PART 8 Packaging Instructions



- Standard: 5m/roll, custom lengths supported
- No heavy stacking / stepping on cartons
- Check goods first if outer box damaged before signing